

The name Workbrutes means more traction, more comfort, and more protection.



**Cleated Outsole:** Spits out debris and provides excellent traction.

### SIZING

<b>Overshoe Size</b>	Men's
X Small	5 - 6½
Small	6½ - 8
Medium	8 - 91/2
Large	<b>9</b> ½ - <b>11</b>
X Large	11 - 13
2X Large	13 - 15

Ideal Applications: Food Processing, Construction, General Industry, Transportation, and Hazardous Waste Cleanup.

### **Chemical Resistance:**

Some exposure to fats, certain acids, hydrocarbons, and caustics. Not recommended for use in ketones, aldehydes, and many solvents.

#4042 4/14



# More Material, More Traction, Longer Wear

## Workbrutes<sup>®</sup> PVC Overshoes Have Thicker And Deeper **Cleats For Better Grip And Longer Wear**

Our injection molded Workbrutes PVC overshoe has 46 percent more material in its outsole than the nearest slush molded competitor. Our Frigiflex<sup>®</sup> PVC compound contains special additives for high stretch and flexibility in cold temperatures.

- Injection molded, seamless construction for 100% waterproof protection.
- Injection molding puts less material in the upper eliminating unnecessary weight, for reduced leg fatigue.
- For longer life more material is added to the sole at the greatest wear points: the heel, toe, and cleats.
- Thicker tread has deeper cleats with sharper edges for more traction.
- Key interior entry points are specially textured to allow overshoes to easily slip on and off over rubber sole shoes.
- Boots feature no-pinch molded in button and two button holes for better fit and protection.
- Heavy duty heel kick-off for easy off.

### **PVC OVERSHOES HI-TOP WORK STYLE – COVERS WORK SHOE UP TO ANKLE** XS – 2XL 35111 Black – Cleated Outsole 35113 Yellow – Cleated Outsole XS – 2XL 10" WORK BOOT - MOLDED IN BUTTON FOR SECURE CLOSURE 35121 Black – Cleated Outsole XS – 2XL 35123 Yellow – Cleated Outsole S - 2XL14" KNEE BOOT - MOLDED IN BUTTON FOR SECURE CLOSURE 35141 Black – Cleated Outsole S – 2XL

Workbrutes® and Frigiflex® are registered trademarks of Tingley Rubber Corp.

ISO 9001 Certified www.tingleyrubber.com 800•631•5498 fax 866•757•9239

